

PERFORATED PLATE - ROUND AND SLOTTED APERTURES					
MILD STEEL - ROUND HOLE					
APERTURE	PITCH	THICKNESS	LENGTH	WIDTH	MATERIAL
0,8	1,5	1	2450	1225	MS
0,8	1,5	0,5	2450	1000	MS
0,8	1,5	0,5	2450	1225	MS
0,8	1,7	0,5	2450	1225	MS
0,8	1,8	0,5	2450	1225	MS
1.0	2.0	0.5	2450	1225	MS
1.0	2.0	0.8	2450	1225	MS
1	2,4	1	2450	1225	MS
1,25	2,3	0,8	2450	1225	MS
1,25	2,3	1,0	2450	1000	MS
1,25	2,3	1,0	2450	1225	MS
1,25	2,4	0,8	2450	1225	MS
1,25	2,4	1	2450	1225	MS
1,6	3,2	0,5	2450	1225	MS
1,6	3,2	1,0	2450	1225	MS
1,6	3,2	1,2	2450	1225	MS
2.0	4.0	1.5	2450	1225	MS
2.0	4.0	2	2450	1225	MS
2,0	3,2	1,0	2450	1225	MS
2,0	3,2	1,5	2450	1225	MS
2,0	3,5	1,2	2450	1225	MS
2,0	3,5	1,5	2450	1225	MS
2,5	4	1	2450	1225	MS
2,5	4	1,2	2450	1225	MS
2,5	5	2	2450	1225	MS
3,2	5,25	0,6	2450	1225	Electro Galv
3,2	5,25	0,8	2450	1225	Electro Galv
3,2	5,25	3	2450	1225	MS
3,2	5,25	1,5	2450	1225	MS
3,2	5,25	1,2	2450	1225	MS
3,2	5,25	1,0	2450	1225	MS
3,2	5,25	2	2450	1225	MS
3.2	5.25	0.8	2450	1225	MS
3.2	5.25	3.0	2450	1225	MS
3,2	5,5	1,5	2450	1225	MS
3,2	5,5	3	2450	1225	MS
3.5	5.0	0.8	1495	750	MS
3.5	5.0	0.8	995	740	MS
4	8	1,5	2450	1225	MS
4,0	8	3	2450	1225	MS
4,0	8	1,0	2450	1225	MS
4,0	8	1,2	2450	1225	MS
4.0	7	1.5	2450	1225	MS
4.0	7	2	2450	1225	MS

4.0	7	3.0	2450	1225	MS
5.0	8.0	1.2	2450	1225	MS
5.0	8.0	1.5	2450	1225	MS
5.0	8.0	3.0	2450	1225	MS
5,0	7,94	3	2450	1225	MS
5,0	7,94	1,5	2450	1225	MS
5,0	7,94	1,0	2450	1225	MS
6,0	11,1	3	2450	1225	MS
6,35	8	1,0	2450	1225	MS
6,35	12,7	4,0	2450	1225	MS
6,35	11,1	0,8	2450	1225	Electro Galv
6,35	11,1	1,2	2450	1225	MS
6,35	11,1	1,5	2450	1225	MS
6,35	11,1	2,0	2450	1225	MS

MILD STEEL - ROUND HOLE					
APERTURE	PITCH	THICKNESS	LENGTH	WIDTH	MATERIAL
6,35	11,1	6,0	2450	1225	MS
6.35	11.1	3.0	2450	1225	MS
6.5	8.0	1.2	2450	1225	MS
6.5	8.0	0.8	1495	750	MS
6.5	8.0	0.8	1495	565	MS
6.5	8.0	0.8	995	740	MS
7,5	10	1,0	2450	1225	MS
8 Square	10	1,5	2450	1225	MS
8,0	10	1,0	2450	1225	MS
8,0	10	1,2	1495	750	MS
8,0	10	1,2	1495	565	MS
8,0	14,29	4,5	2450	1225	MS
8,0	11,1	1,0	2450	1225	MS
8,0	11,1	1,5	2450	1225	MS
8,0	11,1	2,0	2450	1225	MS
8.0	11.1	3.0	2450	1225	MS
8.0	12	1,5	2450	1225	MS
8.0	12	3	2450	1225	MS
8.0	14.29	5.0	2450	1225	MS
8.0	14.29	6.0	2450	1225	MS
8,5	12	1,0	2450	1225	MS
9,0	12	1,0	2450	1225	MS
10,0	12	1,0	2450	1225	MS
10,0	12	1,5	2450	1225	MS
10,0	16	4,5	2450	1225	MS
10.0	12	2.0	2450	1225	MS
10.0	13	3.0	2450	1225	MS
10.0	15,88	1,5	2450	1225	MS
10.0	15.88	6.0	2450	1225	MS
12,0	15	1,0	2450	1225	MS
12,0	16	1,5	2450	1225	MS
12,0	16	2,0	2450	1225	MS
12.7	16.0	1.5	2450	1225	MS
12.7	16.0	2.0	2450	1225	MS
12.7	16.0	3.0	2450	1225	MS
12.7	16.0	6.0	2450	1225	MS
12,7	16	6	2450	1225	MS

12,7	19	6	2450	1225	MS
14,0	17	1,0	2450	1225	MS
14,3	20,64	4,5	2450	1225	MS
16,0	19	1,0	2450	1225	MS
16,0	23,8	3,0	2450	1225	MS
19,05	22	1,0	2450	1225	MS
19,05	28	3	2450	1225	MS
19,05	28,58	3,0	2450	1225	MS
19,05	28,58	6,0	2450	1225	MS
25,0	30	1,0	2450	1225	MS
25,0	35	1,5	2450	1225	MS
25,4	38,1	3,0	2450	1225	MS

MILD STEEL - SLOTTED APERTURES					
APERTURE	PITCH	THICKNESS	LENGTH	WIDTH	MATERIAL
(1,4x20)	23/4	1,0	2450	1225	MS
(1,6x20)	23/4	1,2	2450	1225	MS
(1,8x20)	23/5	1,2	2450	1225	MS
(2x20)	23/5	1,2	2450	1225	MS
(2,2x20)	23/5	1,2	2450	1225	MS
(2,5x20)	23/5	1	2450	1225	MS
(3,0x20)	23/6	1	2450	1225	MS
(3,25x20)	23/6	1	2450	1225	MS
(3,5x20)	23/6	1	2450	1225	MS
(4,0x20)	23/7	1	2450	1225	MS
(4,25x20)	23/7	1	2450	1225	MS
(4,5x20)	23/7	1	2450	1225	MS
(5,0x20)	23/8	1	2450	1225	MS
(6,0x20)	23/9	1	2450	1225	MS
(6,5x20)	23/9	1	2450	1225	MS
(8x20)	25/13	5	2450	1225	MS
(6,0x20)	23/9	2,0	2450	1225	MS
(6,0x26)	29/9	2,0	2450	1225	MS